



NOTES:

- 1 "CRESNET" CABLE:
(1) PAIR #18AWG,
(1) TWISTED PAIR 22AWG
W/SHIELD (BY E.C.)
NON-PLENUM PN: CRESNET-NP-TL
PLENUM PN: CRESNET-P-TL
- 2 RS-232 CABLE:
(1) TWISTED PAIR 22AWG
(1) SHIELD
DB-9 CONNECTOR
(BY E.C.)
- 3 CABLE:
(1) TWISTED PAIR 18AWG
(1) SHIELD
(BY E.C.)
- 4 CABLE:
CAT5E ETHERNET

***ALL PHYSICAL DEVICE LOCATIONS TO BE COORDINATED WITH ARCHITECT.

CRESNET WIRING RUNS SHOWN AS HOME RUN TO EACH DEVICE FOR OPTIMAL PERFORMANCE. DAISY CHAIN AND OR STAR TOPOLOGIES ARE PERMITTED TO SUIT INSTALLATION NEEDS. TOTAL END TO END WIRE LENGTH NOT TO EXCEED 500'.

REVISIONS	DATE	BY
00	12-03-08	VB

PROJECT:	120V 24-CKT DIMMING SYSTEM
LOCATION:	
QUOTE #:	PO #:
SALES REP:	
DISTRIBUTOR:	

CRESTRON
 15 Volvo Drive
 Rockleigh NJ 07647
 Tel: 888-273-7876
 Fax: 201-767-6011
 www.crestron.com

TITLE:
 ONE-LINE
 RISER
 (FOR INFORMATION
 ONLY)

DRAWING:
 1.0