



**NOTES:**

- 1 "CRESNET" CABLE:  
(1) PAIR #18AWG,  
(1) TWISTED PAIR 22AWG  
W/SHIELD (BY E.C.)  
NON-PLENUM PN: CRESNET-NP-TL  
PLENUM PN: CRESNET-P-TL
- 2 RS-232 CABLE:  
(1) TWISTED PAIR 22AWG  
(1) SHIELD  
DB-9 CONNECTOR  
(BY E.C.)
- 3 CABLE:  
(1) TWISTED PAIR 18AWG  
(1) SHIELD  
(BY E.C.)
- 4 CABLE:  
CAT5E ETHERNET

\*\*\*ALL PHYSICAL DEVICE LOCATIONS TO BE COORDINATED WITH ARCHITECT.

CRESNET WIRING RUNS SHOWN AS HOME RUN TO EACH DEVICE FOR OPTIMAL PERFORMANCE. DAISY CHAIN AND OR STAR TOPOLOGIES ARE PERMITTED TO SUIT INSTALLATION NEEDS. TOTAL END TO END WIRE LENGTH NOT TO EXCEED 500'.

REVISIONS	DATE	BY
00	12-03-08	VB

PROJECT:	120V 24-CKT SWITCHING SYSTEM
LOCATION:	
QUOTE #:	PO #:
SALES REP:	
DISTRIBUTOR:	

**CRESTRON**  
 15 Volvo Drive  
 Rockleigh NJ 07647  
 Tel: 888-273-7876  
 Fax: 201-767-6011  
 www.crestron.com

TITLE:  
ONE-LINE RISER (FOR INFORMATION ONLY)  
DRAWING:  
1.0