



NOTES:

1. ACTUAL MAXIMUM SHADE SIZE IS DEPENDENT UPON THE FABRIC CHOSEN.
2. SHADE WIDTH NOT INCLUDED END CAP AT BOTH END.
3. ALL EXTRUSIONS (FASCIA, CLOSURE PLATE, TOP/BACK COVER, ETC.) FOR SHADES INDICATED AS "OUTSIDE MOUNT", 3/16" HAS BEEN DEDUCTED FROM THE WIDTH OF THE EXTRUSION TO ALLOW FOR ENDCAPS. PLEASE VERIFY MESUREMENTS.
4. WIDTH TO HEIGHT RATIO WHICH EXCEEDS 1:4 A STABILIZING BATTEN WILL ASSIST IN REDUCING FABRIC CURLING ON THE SIDES OF THE SHADE. THE DEFAULT BATTEN PLACEMENT IS AT 1/2 WAY POINT OF THE SHADE HEIGHT.

MOTOR	MINIMUM LIGHT GAP		B TO B		MAX. MOTOR CAPACITY
	TUBE	DEDUCTION	MIN.	MAX.	
CSM-QMTDC-163-1-EX	1.63" Spline	3/4"	17 1/2"	96"	3/4 Nm
CSM-QMTDC-163-1-CN					

**ARCHITECTURAL 3 SERIES DUAL SHADE
SHADE ELEVATION**



15 VOLVO DRIVE
 ROCKLEIGH NJ 07647
 TEL: 888-273-7876
 WWW.CRESTRON.COM

DWG. #	M3D6-001
SCALE:	6" = 1'-0"
DATE:	02.27.15
REV.:	