



NOTES:

1. ACTUAL MAXIMUM SHADE SIZE IS DEPENDENT UPON THE FABRIC CHOSEN.
2. SHADE WIDTH NOT INCLUDED END CAP AT BOTH END.
3. ALL EXTRUSIONS (FASCIA, CLOSURE PLATE, TOP/BACK COVER, ETC.) FOR SHADES INDICATED AS "OUTSIDE MOUNT", 3/16" HAS BEEN DEDUCTED FROM THE WIDTH OF THE EXTRUSION TO ALLOW FOR ENDCAPS. PLEASE VERIFY MESSAGES.
4. WIDTH TO HEIGHT RATIO WHICH EXCEEDS 1:4 A STABILIZING BATTEN WILL ASSIST IN REDUCING FABRIC CURLING ON THE SIDES OF THE SHADE. THE DEFAULT BATTEN PLACEMENT IS AT 1/2 WAY POINT OF THE SHADE HEIGHT.

MINIMUM LIGHT GAP			B TO B		MAX. MOTOR CAPACITY
MOTOR	TUBE	DEDUCTION	MIN.	MAX.	
CSM-QMTDC-250-2-EX	2.5" Spline	3/4"	18 15/16"	TBD	3/4 Nm
CSM-QMTDC-250-2-CN					

**ARCH 5 SERIES DUAL SHADE
SINGLE BAND WITH SIDE CHANNEL
SHADE ELEVATIONS**



15 VOLVO DRIVE
ROCKLEIGH NJ 07647
TEL: 888-273-7876
WWW.CRESTRON.COM

DWG. # MA5D-602
SCALE: 6" = 1'-0"
DATE: 10.30.2015
REV.: