

Crestron Virtual Control Server Software

Crestron VIRTUAL CONTROL

- Offers a centralized server-based alternative to individual hardware-based control systems
- Provides a virtual control system for each room
- Streamlines deployment, maintenance, and management
- Supports XiO Cloud® cloud-based monitoring
- Supports C#, SIMPL, and SIMPL# Pro programming
- Integrates directly with IP-controllable devices
- Integrates with serial, IR, CEC, and other controllable devices via decentralized control ports on DM®, DM NVX®, and other Crestron® interfaces
- Enables server redundancy for increased reliability
- Employs enterprise-grade security to ensure maximum reliability and privacy
- Per-room licensing makes it easy to determine the number of licenses required for an installation

Crestron® Virtual Control (VC-4) is a server-based control platform for enterprise applications that can be used in place of hardware-based Crestron control systems. The platform runs programs to control multiple rooms over the network from a single, centralized location. Cloud-based monitoring is also available using the [XiO Cloud®](#) service.

Crestron Virtual Control can be integrated with a variety of devices, including audio, video, lighting, motorized shades, thermostats, door locks, sensors, and security systems. Connected devices can be controlled directly via Ethernet, and those that require a serial, IR, or other hardware interface can be integrated via decentralized control ports on a [DM NVX®](#) encoder/decoder, [DM®](#) transmitter or receiver, [CEN-CI3](#) series interface, or the [CEN-IO wired](#) and [wireless](#) series of I/O modules. Cresnet® network devices can be integrated via a [DIN-CENCN-2](#) bridge, and wireless Crestron devices can also be integrated via an [infiNET EX®](#) wireless gateway.

Crestron Virtual Control supports server redundancy for increased reliability. For large buildings, Crestron Virtual Control streamlines deployment and maintenance by allowing a single program to be deployed across multiple rooms. Support for C#, [SIMPL](#), and [SIMPL#Pro](#) programming languages gives programmers design flexibility and enables programs to be shared with hardware-based control systems. Crestron Virtual control also employs enterprise-grade security to ensure maximum reliability and privacy.

Crestron Virtual Control is sold through Authorized Crestron Dealers, and requires installation on a customer-supplied server running a supported Red Hat Enterprise Linux® server operating system.

Licensing

The Crestron Virtual Control licensing model is similar to a traditional hardware purchase model: purchase a specified number of room licenses, and the Crestron Virtual Control installation will run the number of rooms purchased.

NOTE: The VC-4 server requires access to the XiO Cloud® service to validate its licenses. An active XiO Cloud account is required, subject to the terms of the Crestron Cloudware License Agreement¹. However, a paid XiO Cloud subscription is not required to manage licenses for a VC-4 server. For more information, refer to the [XiO Cloud feature page](#).

Use the [provided form](#) to add Crestron Virtual Control licenses to your XiO Cloud service account.

Model

VC-4-ROOM

Crestron Virtual Control Server Software - Single-Room License

Available Accessories

For a list of available accessories, visit the [VC-4-ROOM](#) product page.

Note:

1. The XiO Cloud® service is licensed under Crestron's Cloudware License Agreement, available at www.crestron.com/Legal/software-products-on-premises-and-cloudware/cloudware-license-agreement.

Crestron Virtual Control Server Software

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is licensed under Crestron's On Premises Software License and Maintenance Agreement, available at www.crestron.com/Legal/software-products-on-premises-and-cloudware.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, Cresnet, DM, DM NVX, infiNET EX, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. AlmaLinux OS is either a trademark or a registered trademark of the AlmaLinux OS Foundation in the United States and/or other countries. Rocky Linux is either a trademark or a registered trademark of Ctrl IQ, Inc. in the United States and/or other countries. Red Hat Enterprise Linux is either a trademark or a registered trademark of Red Hat, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.

Rev 07/15/22

Crestron Virtual Control Server Software

Minimum Server Requirements

Operating System Red Hat Enterprise Linux® 8.2 software (64-bit version) or greater;
AlmaLinux OS® 8.3 software (64-bit version) or greater;
Rocky Linux™ OS 8.4 software (64-bit version) or greater

NOTE: Version 9.x of any of the listed operating systems is not currently supported.

Network Interface 1 Gbps
Hard Drive 100 GB
Disk Space 100 GB

CPU Cores Required

	Average Devices Per Room																			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
50	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	8	8	8
100	4	4	4	4	4	4	4	4	4	8	8	8	8	8	8	8	8	8	16	16
200	4	4	4	4	8	8	8	8	8	16										
300	4	4	8	8	8	8														
400	4	4	8	8	16															
500	4	8	8	16																

RAM (GB) Required

	Average Devices Per Room																			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
50	4	4	8	8	8	16	16	16	16	16	32	32	32	32	32	32	32	32	32	32
100	4	8	16	16	16	32	32	32	32	32	32	64	64	64	64	64	64	64	64	64
200	8	16	32	32	32	64	64	64	64	64										
300	16	32	32	64	64	64														
400	16	32	64	64	64															
500	16	32	64	64																