

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity



- *Two HDMI® and two USB-C® inputs*
- *4K60 4:4:4 video over standard Gigabit Ethernet, configurable as an encoder or decoder¹*
- *Support for 5K Ultra-Wide (21:9) and Super-Wide (32:9) resolutions*
- *HDR10, HDR10+, and Dolby Vision® video support*
- *Real-time video performance over the network with Pixel Perfect Processing technology*
- *H.264 encoding and streaming*
- *Enterprise-grade security including 802.1X, Active Directory® credential management, TLS, and AES-128*
- *One HDMI output with 5K scaler*
- *eARC support available on HDMI® connection to display and secondary HDMI input*
- *Video wall processing*
- *Dynamic text overlay capability*
- *7.1 surround sound audio support*
- *AES67 and analog audio embedding and de-embedding*
- *Copper or fiber Ethernet connectivity*
- *USB 2.0 and KVM signal extension and routing*
- *Device control via CEC*
- *Automatic point-to-point connectivity*
- *Easy setup via built-in web interface*
- *Interoperability with a Crestron 3-Series® or later control system*
- *Streamlined management using DM NVX Director™ virtual switching appliances*
- *Crestron XiO Cloud™ service support*
- *Designed for installation into a [DMF-CI-8](#) card chassis*

The [DM-NVX-384C](#) is a DM NVX® AV-over-IP encoder/decoder card that occupies one card slot in a [DMF-CI-8](#) card chassis. The card is designed to function as either a transmitter or receiver in a high-density rack-mount installation. Capable of handling a network AV installation of any size, the DM-NVX-384C includes features such as secure web-based control and management, a scaling HDMI output, video wall processing, an analog audio input or output⁵, native AES67 transmit and receive capability, surround sound audio, support for copper and fiber-optic Ethernet connectivity, and USB 2.0 and KVM integration.^{2,3}

HDMI® and USB-C® 4x1 Input Auto-Switching

The DM-NVX-384C includes two HDMI inputs and two USB-C inputs that comprise a 4x1 input switcher. Switching between the four inputs can be performed automatically using auto-switching mode, programmatically via a control system, or through the web interface. When mounted behind a conference room display device, the HDMI input provides a convenient way to connect a Crestron [AirMedia®](#) presentation gateway, video-conferencing codec, or small form factor computer. The USB-C inputs allow for a DisplayPort™ Alt Mode video connection to laptops that do not feature an HDMI connection. The USB-C connectors also pass USB 2.0 data back and forth from the host PC and other DM NVX or DM NUX endpoints.

eARC Support

The HDMI output of the DM-NVX-384C supports Enhanced Audio Return Channel (eARC) connectivity, enabling audio to be extracted from a connected display and transmitted over the network as a multichannel BTS audio-over-IP stream. Extracting audio from the display via the eARC connection means only a single cable is required for A/V input and audio output. This also makes local audio content from the display (such as smart TV streaming applications) available to an AoIP audio distribution system.

The secondary HDMI input supports eARC as an audio output to pass content from a multichannel AoIP stream to the HDMI output of a connected AVR. The BTS multichannel AoIP stream generated by the DM NVX endpoint is also compatible with the [DM-NAX-XSP](#) (sold separately) for zones where video transmission is not required.

Real-Time Video Distribution

DM NVX technology ensures real-time, full-motion 4K60 and 5K video performance for the presentation of multimedia, videoconferencing, and live camera images. Interactive functions such as gameplay and using a mouse are fluid and natural. Line-synchronized outputs ensure synchronization of content across multiple displays for applications such as digital signage and video walls. Variable Multicast TTL (Time To Live) enables traversing multiple network routers.

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity

Support for 5K Resolutions

The DM-NVX-384C includes support for 5K Ultra-Wide 5120 x 2160 and 5K Super-Wide 5120 x 1440 video resolutions, expanding the DM NVX product family's compatibility with the latest generation of computers, monitors, and displays.

Pixel Perfect Processing Technology

A DM NVX system incorporates Pixel Perfect Processing technology, which provides flawless video transport in all applications. Depending on the operating mode, the DM-NVX-384C can encode or decode a video signal to achieve imperceptible end-to-end latency of less than one frame. The image quality of the source is maintained across a 1-Gigabit network at resolutions up to 5K Ultra-Wide 4:4:4.

H.264 Streaming

H.264 encoding is supported on the DM-NVX-384C while in transmitter mode via an additional network stream. 1080p H.264 video can be distributed from one DM NVX device to multiple network decoders at up to 10-bit 4:2:2 color-depth and chroma subsampling. This enables streaming video directly from a DM NVX device to Crestron touch screens or digital graphics engines, or a broad range of third-party H.264-enabled devices.

Enterprise-Grade Security

Using advanced security features and protocols such as 802.1X authentication, Active Directory® credential management, AES-128 content encryption, PKI authentication, TLS, SSH, and HTTPS, a DM NVX system delivers a true enterprise-grade network AV solution engineered to fulfill demanding IT policies.

Encoder and Decoder Functionality

The DM-NVX-384C is configurable to operate as either a network AV encoder or decoder. As an encoder, the connected media source can be transmitted over the network to one or many decoders. As a decoder, the device feeds the received signal to a connected display device, and can quickly switch between multiple encoder feeds. The operating mode can be reconfigured dynamically in less than 1 minute via a control system or web browser.

HDMI Output with 5K Scaler

Whether configured as an encoder or decoder, the built-in scaler ensures an optimal image, scaling the encoded source resolution up or down to match the native resolution of the display device.⁴

Video Wall Processing

A video wall composed of up to 64 individual displays can be configured using multiple DM NVX endpoints. Each endpoint provides fully adjustable zoom capability and bezel compensation to accommodate a range of video wall configurations and display types. One DM NVX endpoint is

required per display, supporting configurations of up to eight wide by eight high.

Text Overlay

The ability to display dynamic or fixed text on screen provides a means to label the video source or to display special instructions, schedules, announcements, alerts, and other messaging.

7.1 Surround Sound Audio

DM NVX technology supports the lossless transport of 7.1 surround sound audio signals, including Dolby® TrueHD, Dolby Atmos®, DTS HD®, DTS:X®, and uncompressed linear PCM. In decoder mode, the DM-NVX-384C can receive both multichannel and 2-channel downmix signals from a [DM-NVX-363](#), [DM-NVX-363C](#), [DM-NVX-351](#), or [DM-NVX-351C](#) encoder, allowing either signal to be selected at the HDMI output while the 2-channel signal is automatically routed to the analog output.

AES67 and DM NAX® Audio Embedding and De-embedding

AES67 support via native support for Crestron DM NAX® Audio-over-IP technology allows the selected audio source to be transmitted as a 2-channel AES67 source while another AES67 2-channel audio stream is received from a Crestron DM NAX device or other AES67 capable device and combined with the video signal.

In DM NVX encoder mode, the received AES67 audio stream can be output via the local HDMI output, primary AV stream, secondary audio stream, and analog audio output. In DM NVX decoder mode, the AES67 received audio stream can be combined with the video and then output via the HDMI output and analog audio output.

Analog Audio Embedding or De-embedding

An unbalanced stereo analog audio port is included, which can be configured as either an input or output. As an input, the port allows a stereo audio source to be connected and combined with the video signal from the HDMI input or the incoming network video stream. As an output, the port can provide a stereo line-level signal to feed a local sound system or soundbar. The output volume is adjustable via a control system or web browser.⁵

Breakaway Audio

A DM NVX decoder can select and combine separate video and audio signals from two different inputs or even two different encoders. Combining signals from two separate encoders is limited to 2-channel stereo audio.⁶

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity

Copper or Fiber Ethernet Connectivity

The DM-NVX-384C includes two RJ-45 1000BASE-T ports (Ethernet ports 1 and 2) and one SFP port (Ethernet port 3). Any Ethernet port can be used to transport video over a Gigabit Ethernet network. The ports can also be used to daisy-chain multiple endpoints feeding a single-source video wall or individual displays that show the same video image.²

A DM NVX system can be deployed on an existing corporate or campus network or on a dedicated network. For information about network requirements and guidelines, refer to the [DM NVX AV-over-IP System Design Guide](#).

USB 2.0 and KVM Integration

DM NVX technology supports the extension of USB signals, which can be switched and routed alongside the AV signal or separately via a control system. USB 2.0 ports are provided on the DM-NVX-384C, allowing a USB mouse, keyboard, or other peripheral device to be connected to a remote endpoint and routed to a computer or other host at the local endpoint.⁷

USB 2.0 Layer 3 data transport supports USB signal extension in DM NVX point-to-point applications across VLANs.

Web-Based Setup

Setup of the DM-NVX-384C is accomplished by using a web browser. Full control and monitoring of the device is enabled through integration with a control system or with a DM NVX Director® virtual switching appliance.

Streamlined Management Using DM NVX Director® Virtual Switching Appliances

Use of a DM NVX Director® virtual switching appliance ([DM-NVX-DIR-80](#), [DM-NVX-DIR-160](#), or [DM-NVX-DIR-ENT](#)) streamlines the configuration and control process. A DM NVX Director appliance provides a central point of management and enables the creation of multiple virtual matrix switchers through one easy-to-use web-based portal.

Crestron XiO Cloud® Service Support

The DM-NVX-384C is compatible with the Crestron XiO Cloud® service for remote provisioning, monitoring, and managing. This service enables installers and IT managers to deploy and manage thousands of devices simultaneously. Refer to crestron.com/xiocloud for more information.

High-Density, Card-Based Solution

The DM-NVX-384C is designed for installation into a [DMF-CI-8](#) card chassis, providing a scalable high-density solution for applications requiring multiple encoders and decoders in one equipment rack.

Refer to the [DM NVX feature page](#) for additional design tools and reference documents.

Specifications

Encoding/Decoding

Video Codec	Encoder: Pixel Perfect Processing (default) or DM-NVX-D10/D20/D200 ⁹ , H.264 AV-over-IP streaming; Decoder: Pixel Perfect Processing or DM-NVX-D10/D20 ⁹
Video Resolutions	Up to 5120x2160 @30 Hz (5K Ultra-Wide) or 5120x1440 @60 Hz (5K Super-Wide); Up to 4:4:4 color sampling; HDR10, HDR10+, Dolby Vision, and Deep Color support
Audio Formats	Primary multichannel (up to 8-channel LPCM or encoded HBR 7.1 surround sound), secondary 2-channel LPCM ¹⁰
Bit Rates	200 to 950 Mbps ⁸
Streaming Protocols	RTP, SDP
Container	MPEG-2 transport stream (.ts)
Session Initiation	Multicast via secure RTSP
Copy Protection	HDCP 2.3, AES-128, PKI

Video

Input Signal Types	HDMI with HDR10, HDR10+, Dolby Vision, Deep Color, and 5K support ^{1, 11} (Dual-Mode DisplayPort™ interface and DVI compatible ¹²) DisplayPort over USB-C (DisplayPort Alt Mode) ¹³ with HDR10, HDR10+, and 5K support
Output Signal Types	HDMI with HDR10, HDR10+, Dolby Vision, Deep Color, and 5K support ¹ (DVI compatible ¹²)
Switcher	4x1 in encoder mode (Two HDMI, Two USB-C), manual or auto-switching, breakaway audio, ⁶ Crestron QuickSwitch HD™ technology 5x1 in decoder mode (HDMI, Stream), manual or auto-switching, breakaway audio, ⁶ Crestron QuickSwitch HD™ technology
Scaler (Decoder Mode Only)	5K video scaler with motion-adaptive deinterlacing, intelligent frame rate conversion, Deep Color support, HDR10, HDR10+, and Dolby Vision support, widescreen format selection (zoom, stretch, maintain aspect ratio, or 1:1), video wall processing up to 8 wide x 8 high, static or dynamic text overlay

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity

Copy Protection

HDCP 2.3

Maximum Resolutions

Common resolutions are shown in the following table. Custom resolutions are supported at pixel clock rates up to 600 MHz.

Scan Type	Resolution	Frame Rate	Color Sampling	Color Depth
Progressive	5120x2160 5K Ultra-Wide	30 Hz	4:4:4	8 bit
	5120x2160 5K Ultra-Wide*	60 Hz	4:2:0	8 bit
	5120x1440 5K Super-Wide	60 Hz	4:4:4	8 bit
	4096x2160 DCI 4K and 3840x2160 4K UHD	30 Hz	4:4:4	12 bit
		60 Hz	4:2:0	12 bit
		60 Hz	4:2:2	12 bit
		60 Hz	4:4:4	8 bit
	2560x1600 WQXGA Reduced Blanking	60 Hz	4:4:4	8 bit
	2560x1440 WQHD Reduced Blanking	60 Hz	4:4:4	8 bit
		120 Hz	4:4:4	8 bit
	2560x1080 UWFHD	60 Hz	4:4:4	8 bit
	2048x1152 QWXGA	60 Hz	4:4:4	12 bit
	2048x1080 DCI 2K	60 Hz	4:4:4	12 bit
	1600x1200 UXGA	60 Hz	4:4:4	12 bit
	1920x1200 WUXGA	60 Hz	4:4:4	12 bit
1920x1080 FHD 1080p	60 Hz	4:4:4	12 bit	
	120 Hz	4:4:4	8 bit	
	240 Hz	4:4:4	8 bit	
Interlaced (Input Only)	1920x1080 HD 1080i	30 Hz	4:4:4	12 bit

*5K Ultra-Wide @60Hz 4:2:0 is supported as an unscaled pass-through resolution only.

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity

Audio	
Input Signal Types	HDMI (Dual-Mode DisplayPort interface compatible ¹²), DisplayPort over USB-C (DisplayPort Alt Mode), ¹³ eARC (via HDMI OUT), AES67 (2-channel), BTS (multichannel network stream), analog stereo ⁵
Output Signal Types	HDMI (multichannel pass-through), eARC (via HDMI IN 2), AES67 (2-channel), BTS (multichannel network stream), analog stereo (2-channel)
Digital Formats	Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos, DTS®, DTS ES, DTS 96/24, DTS HD High Res, DTS HD Master Audio, DTS:X, LPCM up to 8 channels
Analog Formats	Stereo 2-channel
Analog-to-Digital Conversion	24-bit, 48 kHz
Digital-to-Analog Conversion	24-bit, 48 kHz
AES67 or DM NAX Audio-over-IP	24-bit, 48 kHz
Analog Performance	Frequency Response: 20 Hz to 20 kHz ±0.5 dB; S/N Ratio: >95 dB 20 Hz to 20 kHz A-weighted; THD+N: <0.005% @ 1 kHz; Stereo Separation: >90 dB
Analog Output Volume Adjustment	-80 to +20 dB
Communications	
Ethernet	Auto-switching, auto-negotiating, autodiscovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), IEEE 802.1X, IPv4, IPv6, Active Directory authentication, variable Multicast TTL, HTTPS web browser setup and control, Crestron 3-Series or later control system integration
USB	USB 2.0 host or device signal extension and routing, Layer 2 or Layer 3
HDMI	HDCP 2.3, EDID, CEC, ARC, eARC
USB-C (DisplayPort Alt Mode)¹³	HDCP 2.3, EDID, CEC, USB 2.0
DM NVX (via Ethernet)	HDCP 2.3, AES-128 AV content encryption with PKI authentication, RTP, secure RTSP, SDP, ONVIF, IGMPv2, IGMPv3, SMPTE 2022, FEC (Forward Error Correction)
Connectors	
USB2 TO DEVICE	(1) USB Type-A connector, female; USB 2.0 device port; USB signal extender port for connection to a mouse, keyboard, or other USB 2.0 device; ⁷ Available Power: 500mA at 5 VDC
HID TO DEVICE	(1) USB Type-A connector, female; USB 2.0 device port; USB signal extender port for connection to a USB HID compliant mouse, keyboard, or other USB HID compliant device; Available Power: 500mA at 5VDC
Ethernet 1	(1) 8-pin 8P8C connector, female; 100BASE-TX/1000BASE-T Ethernet port ²
Ethernet 2 (LAN)	(1) 8-pin 8P8C connector, female; 100BASE-TX/1000BASE-T Ethernet port ²
Ethernet 3 (1G SFP)	(1) SFP port; Accepts one Crestron SFP-1G Series transceiver module ³
HDMI OUT (eARC)	(1) HDMI Type A connector, female; HDMI digital video/audio output ¹ (DVI compatible ¹²); eARC audio return support
HDMI IN 1	(1) HDMI Type A connector, female; HDMI digital video/audio input; ¹ (DVI and Dual-Mode DisplayPort interface compatible ¹²)
HDMI IN 2 (eARC)	(1) HDMI Type A connector, female; HDMI digital video/audio input; ¹ (DVI and Dual-Mode DisplayPort interface compatible ¹²); eARC audio output support
TO HOST DP-S USB2 (IN 3-4)	(2) USB Type-C® connectors, female; USB 2.0 host ports; USB signal extender ports for connection to a computer or other USB 2.0 host; DisplayPort single stream video inputs ¹³

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity

AUDIO I/O	(1) 3-pin 3.5 mm detachable terminal block; Unbalanced stereo line-level audio input or output; ⁵ Input Impedance: 24 kΩ; Maximum Input Level: 2Vrms; Output Impedance: 100 Ω; Maximum Output Level: 2Vrms
------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Controls and Indicators

OL	(1) Green LED, indicates an online connection to a control system via Ethernet
TX	(1) Green LED, indicates unit is in encoder (transmitter) mode
RX	(1) Green LED, indicates unit is in decoder (receiver) mode
Ethernet 1-3	(2) LEDs per port; Green indicates Ethernet link status; Amber indicates Ethernet activity
HDMI OUT	(1) Green LED, indicates video signal transmission at the HDMI output
HDMI IN 1-2	(2) Green LEDs, indicates sync detection at the HDMI inputs

Environmental

Temperature	32° to 104°F (0° to 40°C)
Humidity	10% to 90% RH (noncondensing)

Construction

Plug-in card, occupies (1) card slot in a [DMF-CI-8](#) card chassis, includes metal faceplate

Weight

1.2 lb (0.54 kg)

Compliance

Regulatory Model: M202234002

FCC Part 15 Class B, IC Class B, CE, Intertek® Listed for US and Canada

Model

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity

Available Accessories

For a list of available accessories, visit the [DM-NVX-384C](#) product page.

Management Tools

DM-NVX-DIR-80

DM NVX® Director® Virtual Switching Appliance for 80 Endpoints

DM-NVX-DIR-160

DM NVX® Director® Virtual Switching Appliance for 160 Endpoints

DM-NVX-DIR-ENT

DM NVX® Director® Virtual Switching Appliance for 1000 Endpoints

Notes:

- 5K performance and HDR support require the use of HDMI cables and couplers with a minimum TMDS bandwidth of 18 Gbps. If 4K60 4:2:0 or 4K30 4:4:4 performance is acceptable, cables and couplers with a minimum bandwidth of 10.2 Gbps may be used. Bandwidth loss is cumulative; therefore, performance may be reduced when inserting multiple cables and couplers inline.
- The minimum cable required for DM NVX over 1000BASE-T Ethernet (copper) is unshielded CAT5e. All Ethernet ports on the DM-NVX-384C are for connection to an Ethernet network or device. The Ethernet ports cannot be connected to the DM® ports of other Crestron DigitalMedia™ devices.
- Use of the SFP port requires the purchase of a Crestron SFP-1G Series transceiver module (sold separately). All Ethernet ports on the DM-NVX-384C are for connection to an Ethernet network or device. The Ethernet ports cannot be connected to the DM® ports of other Crestron DigitalMedia™ devices.
- When the DM-NVX-384C is in encoder mode, the HDMI output resolution is matched to the resolution of the encoded source.
- The analog audio port can function as either an input or output, but not both.
- Combining audio from one encoder with video from another encoder is possible using the secondary 2-channel audio stream only. Multichannel audio from one encoder cannot be combined with video from another encoder.
- The DM-NVX-384C can accept a USB device or a USB host device connection, not both simultaneously. Crestron DM NVX products are engineered to deliver maximum compatibility with the widest possible range of USB products. Crestron does not guarantee that all USB products are compatible with DM NVX products. Consult the [DM NVX AV-over-IP System Design Guide](#) for USB bandwidth considerations.
- The minimum bit rate for 4K60 video is 350 Mbps. A bit rate below 350 Mbps may display a black screen.

DM-NVX-384C

DM NVX® 5K 4x1 AV-over-IP Switcher Card with HDMI® and USB-C® Connectivity

- In encoder mode, the stream type of the DM-NVX-384C must be set by using the web interface or a control system. The default setting is Pixel Perfect Processing for interoperability with DM NVX 4K60 4:4:4 decoders. For interoperability with a DM-NVX-D10, DM-NVX-D20, or DM-NVX-D200 decoder, the stream type of the DM-NVX-384C encoder must be set to DM-NVX-D10/D20 Series. In addition, the resolution of the encoder must be set so that it does not exceed the maximum resolution of the DM-NVX-D10, DM-NVX-D20, or DM-NVX-D200 decoder.

In decoder mode, the proper stream type of the DM-NVX-384C is automatically used. For interoperability with DM NVX 4K60 4:4:4 encoders, Pixel Perfect Processing is automatically used as the stream type of the DM-NVX-384C decoder. For interoperability with DM-NVX-E10/E20 Series encoders, DM-NVX-D10/D20 Series is automatically used as the stream type of the DM-NVX-384C decoder.

- As an encoder, the DM-NVX-384C transmits audio via the secondary 2-channel stream when it receives a 2-channel stereo input signal via the HDMI or analog input. The DM-NVX-384C does not transmit audio via the secondary 2-channel stream when it receives multichannel audio.
- 3D formats are not supported.
- HDMI connections require an appropriate adapter or interface cable to accommodate a DVI or Dual-Mode DisplayPort signal. [CBL-HD-DVI](#) interface cables are available separately.
- USB-C connections require USB-C cables that support DisplayPort Alt Mode video in order to pass video signal. Not all USB-C cables can support DisplayPort Alt Mode video.

©2026 Crestron Electronics, Inc.

Rev 05/07/26

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or contact us for additional information by visiting www.crestron.com/contact/our-locations for your local contact.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

The product warranty can be found at www.crestron.com/warranty.

The specific patents that cover Crestron products are listed online at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, 3-Series, .AV Framework, AirMedia, Crestron Home, DigitalMedia, DM, DM NAX, DM NVX, DM NVX Director, QuickSwitch HD, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby, Dolby Atmos, Dolby Digital, and Dolby Vision are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS HD, and DTS:X are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Intertek is either a trademark or registered trademark of Intertek Group in the United States and/or other countries. Active Directory is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. USB-C and USB Type-C are either trademarks or registered trademarks of USB Implementers Forum, Inc. in the United States and/or other countries. DisplayPort is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

HDMI

Specifications are subject to change without notice.

Crestron Electronics Inc.

15 Volvo Drive | Rockleigh, NJ 07647
www.crestron.com | 800.237.2041

