

ULTIMATE IC8-AW-W-T-EACH

Ultimate 8 in. 2-Way All Weather In-Ceiling Speaker, White Textured, Single



- *Audiophile performance 2-way all weather in-ceiling speaker*
- *8 in. (203 mm) carbon fiber woofer*
- *1 in. (25 mm) steerable, ceramic-coated aluminum tweeter*
- *IP66 rated for particle and water protection*
- *Twist and lock toolless bayonet mounting system*
- *150 W (Program), and 300 W (Peak) power handling*
- *45 Hz to 30 kHz (± 3 dB) frequency response*
- *8 Ohms nominal impedance*
- *Various grille options*
- *Installation friendly low profile with 4.63 in. (118 mm) depth*

Crestron® Ultimate speakers made by Origin Acoustics deliver the pinnacle of performance for demanding residential installations. Select materials, top shelf components and a high-end appearance underscore the design behind each model. The result is a complete line of in-ceiling speakers suitable for installation in multiple locations. Weatherized construction allows for use in deck, patio, locker room, sauna, yacht, and swimming pool areas.

The ULTIMATE IC8-AW-W-T-EACH promises the best in installed audio design, delivering stunning sound quality while minimizing impact to the customer's decor. The in-ceiling speaker is provided with a round grille with white plastic bezel. Square and/or aluminum-colored grille options are sold separately. In addition, the following accessories are available:

- Flush Mount Kit ([SPKA-FMKT-IC6/IC8](#))
- Preconstruction Mounting Kit ([SPKA-PMK-IC6/IC8](#))
- New-Construction Template ([SPKA-NCTP-IC6/IC8](#))
- Fire Rated Back Box ([SPKA-BBFR8-IC6/IC8](#))
- Acoustic Back Can ([SPKA-BC-IC6/IC8](#))

Streamlined installation of the speaker is facilitated through an easy to use twist and lock toolless bayonet mounting system optimized to minimize interference with other elements present in the ceiling space.

NOTE: The Ultimate and Reference IC6 and IC8 speakers are interchangeable as they share the same cutout diameter dimension.

The ULTIMATE IC8-AW-W-T-EACH 2-way all weather in-ceiling speaker features an 8 in. (203 mm) carbon fiber woofer for deep, defined low end and articulate midrange, and a 1 in. (25 mm) ceramic coated aluminum tweeter for crisp highs with consistent coverage across a wide listening area. A compression molded woofer basket assures pure, uncolored bass response. Suspended coaxial mounting of the pivoting tweeter reduces midrange frequency response anomalies caused by interference between the woofer and the back of the tweeter.

Specifications

Features & Performance

Woofer	8 in. (203 mm) carbon fiber
Tweeter	1 in. (25 mm) ceramic coated aluminum; Steerable up to 30° off-axis
Crossover Slope	30 dB/oct
Crossover Point	3.5 kHz
Impedance	8 Ohms nominal
Frequency Response	45 Hz to 30 kHz (± 3 dB)
Frequency Range	35 Hz to 30 kHz (± 10 dB)
Power Handling	Program: 150 W; Peak: 300 W
Sensitivity	86 dB @ 1 W/1 m

Connections

Input	2-pin 5.08 mm pitch, 10A, detachable terminal block
Maximum Wire Size	12 AWG (3.31 mm ²)

Environmental

Temperature	4° to 176°F (-15.5° to 80°C)
-------------	------------------------------

ULTIMATE IC8-AW-W-T-EACH

Ultimate 8 in. 2-Way All Weather In-Ceiling Speaker, White Textured, Single

Humidity	10% to 90% RH (non-condensing)
Ingress Protection	IP66 rated for particles and water

Construction

Baffle	Glass fiber reinforced ABS
Grille	Electroplated and powder coated steel, paintable, magnetically held bezel design
Mounting	Toolless bayonet mounting system

Dimensions

Diameter without grille	9.61 in. (244 mm)
Depth	4.63 in. (118 mm) without bayonet ring; Up to 5.30 in. (135 mm) with bayonet ring
Round Grille	10.20 in. (259 mm)
Recommended Cutout Diameter	8.75 in. (222 mm)

Weight

5 lb (2.26 kg)

Compliance

Regulatory Model: M202139001
CE, RoHs, FCC Part 15 Class B digital device

Model

ULTIMATE IC8-AW-W-T-EACH

Ultimate 8 in. 2-Way All Weather In-Ceiling Speaker, White Textured, Single

Available Accessories

For a list of available accessories, visit the [ULTIMATE IC8-AW-W-T-EACH](#) product page.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Origin Acoustics is either a trademark or a registered trademark of Origin Acoustics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2025 Crestron Electronics, Inc.

Rev 11/03/25

ULTIMATE IC8-AW-W-T-EACH

Ultimate 8 in. 2-Way All Weather In-Ceiling Speaker, White Textured, Single

