

SSW-100

Room Availability Hallway Sign, Wall Mount, Enhanced Legibility, Without Engraving



- Provides indication of room availability that is clearly visible from 50 ft (15 m)
- Stylish wall mount design with clear acrylic sign
- Out-of-the-box functionality when used with a TSS-770, TSS-1070, TSW-770(-GV), or TSW-1070(-GV) series touch screen
- Illuminates green or red to clearly indicate the room availability status
- Supports RGB color mixing via custom control system programming to enable virtually any color illumination (except white)
- Custom engraving allows a room name, number, or icon to be featured on the sign
- Custom functionality available when connected to a Crestron control system
- Energy efficient at less than 2 W power consumption
- Single-wire USB or Cresnet® network connectivity
- Mounts to a single-gang electrical box or plaster ring
- Mullion mounting kit available separately
- Projects 8.43 in. (214 mm) from the wall

The [SSW-100](#) hallway sign provides a clear indication of a room's availability with enhanced contrast and visibility as part of a complete Crestron® enterprise room scheduling solution. The SSW-100 features a stylish appearance and vivid color illumination that complements any corporate office environment. The two-sided, clear acrylic sign face illuminates green or red to indicate the room availability status. The sign face is custom engravable with the room number, name, icon, or other designation. The complete sign assembly mounts to the wall over a 1-gang electrical box or plaster ring.

NOTE: The SSW-100 is recommended for existing SSW series installations completed prior to July 2019. For new installations, refer instead to models [SSW-100-EL](#) and [SSW-102-EL](#).

Room Availability Status

For room scheduling applications, the SSW-100 connects via USB to a Crestron [TSS-770](#), [TSS-1070](#), [TSW-770](#), [TSW-770-GV](#), [TSW-1070](#), or [TSW-1070-GV](#) series touch screen. No special programming or configuration is required. The sign color is controlled by the room scheduling application, which runs on the touch screen and syncs with [Crestron Fusion®](#) software or another room scheduling service. The sign illuminates green when the room is available and red when the room is occupied.¹ The clear sign face allows for increased contrast and readability from a distance, making it perfect for environments with long corridors or large, open spaces.

Custom RGB Colors

For custom applications, the SSW-100 can be integrated with a Crestron control system and programmed to illuminate in a variety of colors:

- The RGB LEDs can be controlled in 10% increments per color.
- When the sign is powered by USB, any single color LED can be used at full brightness.
- When the sign is connected to a control system via a Cresnet® network connection, two color LEDs can be used at full brightness simultaneously.
- Three color mixing is possible via Cresnet if each LED is limited to 70%.
- The control system can be programmed to support all types of functionality, enabling colors to alternate, fade in and out, or blink on and off.

Control system integration can be accomplished through a USB connection to a TSS-770, TSS-1070, TSW-770, TSW-770-GV, TSW-1070, or TSW-1070-GV series touch screen, or through a Cresnet connection to the control system.²

Custom Engraving

The SSW-100 includes a blank acrylic sign that supports custom engraving. The engraving appears on both sides of the acrylic sign face to identify the room by name, number, or a representative icon image. When illuminated, the engraving is clearly visible at a distance of 50 ft (15m) if 1 in. fonts are used. Engraving can be changed at any time by purchasing a replacement sign face (models [SSW-ARC-100](#) or [SSW-ACR-102](#)). The SSW-100 engravings generated by [Impress Custom Engraving Software](#) or a third party.

SSW-100

Room Availability Hallway Sign, Wall Mount, Enhanced Legibility, Without Engraving

Simple Installation

The SSW-100 mounts to the wall over a standard 1-gang electrical box or plaster ring. Power and communications are supplied by a single USB or Cresnet cable. A 6 ft (1.83 m) USB cable is included, which connects to the touch screen mounted below the sign. Alternately, a [Cresnet cable](#) (sold separately) can be run to a control system up to 3,000 ft (914 m) away. Cresnet permits multiple hallway signs to be daisy chained using a single cable.^{1,2}

Mullion Mounting Option

When a suitable wall surface is not available, the SSW-100 can be mounted to the mullion of an interior glass wall, window, or partition using the optional [SSW-MUMK](#) mullion mount kit (sold separately). The same kit may also be adhered directly to the glass or any other smooth surface.

NOTE: The SSW may be converted to an [SIW-100](#) Room Availability Status Indicator by replacing the acrylic sign face with an SIW-ACR-100 acrylic indicator lens.

Specifications

Sinage

Material	Acrylic, two sided
Engraving	One or two lines per side with same text or graphical icon on each side
Illumination	Edgelit RGB LED
Functionality	Supports alternating red/green indication of room availability status when connected to a room scheduling touch screen via USB ¹ , supports custom RGB color mixing when connected to a control system ²

Communications

USB	USB 2.0 device for connection to a TSS-770 , TSS-1070 , TSW-770 , TSW-770-GV , TSW-1070 , or TSW-1070-GV series touch screen ¹
Cresnet	Cresnet® network client mode ²

Connectors

CNET	(1) 4-pin 3.5 mm detachable terminal block; Cresnet client port ²
USB	(1) micro USB Type B connector, female; USB 2.0 device port ¹ ; 6 ft (1.83 m) micro B male to A male USB cable included

Controls

CNET ID	(1) Push button (behind bezel) for Cresnet TSID (touch-settable ID)
----------------	---

Power

USB	1.2 W @ 5V USB power ¹
Cresnet Power Usage	2 W @ 24VDC

Environmental

Temperature	41 to 113 °F (5 to 45 °C)
Humidity	10% to 90% RH (noncondensing)
Heat Dissipation	4 BTU/hr on USB power; 7 BTU/hr on Cresnet power

Construction

Composition	Metal bracket with replaceable clear acrylic sign face and magnetically-held gray plastic bezel
Mounting	Mounts to a 1-gang U.S. electrical box or plaster ring (optional mullion mount kit sold separately)

Dimensions

Height	6.41 in. (163 mm)
Width	2.79 in. (71 mm)
Depth	8.57 in. (218 mm)
	<i>Projects 8.43 in. (214 mm) from the mounting surface</i>

Weight

5.7 lb (2.6 kg)

Compliance

UL® Standards Listed for US & Canada, IC, FCC Part 15 Class B digital device

Model

SSW-100
Room Availability Hallway Sign, Wall Mount, Enhanced Legibility, Includes Custom Engraving

SSW-102
Room Availability Hallway Sign, Wall Mount, Enhanced Legibility, Includes Custom Engraving

Available Accessories

For supported accessories, visit the SSW-100 product page at www.crestron.com.

SSW-100

Room Availability Hallway Sign, Wall Mount, Enhanced Legibility, Without Engraving

Notes:

1. The USB port and cable are exclusively for connection to a Crestron® TSS-770, TSS-1070, TSW-770, TSW-770-GV, TSW-1070, or TSW-1070-GV series touch screen. The TSS-1070, TSW-1070, and TSW-1070-GV must be powered using PoE+ (IEEE 802.3at Type 2 Class 4).
2. Control system integration can be accomplished through a USB connection to a TSW-770, TSW-770-GV, TSW-1070, or TSW-1070-GV series touch screen, or through a Cresnet® network connection to the control system. USB and Cresnet connectivity are mutually exclusive. When using USB, the touch screen must be addressable over Ethernet from the control system. Control system integration is not available when connected via USB to a TSS series touch screen.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or contact us for additional information by visiting www.crestron.com/contact/our-locations for your local contact.

The specific patents that cover Crestron products are listed online at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, Cresnet, and Crestron Fusion are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. UL is either a trademark or a registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2025 Crestron Electronics, Inc.

Rev 08/12/25

SSW-100

Room Availability Hallway Sign, Wall Mount, Enhanced Legibility, Without Engraving

