

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing



- Two HDMI® and two USB-C® inputs
- 4K60 4:4:4 video over standard Gigabit Ethernet, configurable as an encoder or decoder<sup>1</sup>
- Support for 5K Ultra-Wide (21:9) and Super-Wide (32:9) resolutions
- HDR10, HDR10+, and Dolby Vision® video support
- Real-time video performance over the network with Pixel Perfect Processing technology
- H.264 encoding and streaming
- Enterprise-grade security including 802.1X, Active Directory® credential management, TLS, and AES-128
- One HDMI output with 5K scaler
- eARC support available on HDMI® connection to display and secondary HDMI input
- Video wall processing
- Dynamic text overlay capability
- 7.1 surround sound audio with downmixing for formats up to Dolby Atmos MAT 2.0 and DTS:X
- AES67 and analog audio embedding and de-embedding
- Copper or fiber Ethernet connectivity
- USB 2.0 and KVM signal extension and routing
- Device control via RS-232, IR, and CEC
- Automatic point-to-point connectivity
- Easy setup via built-in web interface
- Interoperability with a Crestron 3-Series® or later control system
- Streamlined management using DM NVX Director™ virtual switching appliances
- Crestron XiO Cloud™ service support
- Compact, surface- or rack-mountable design
- Powered via PoE++ or optional power pack (sold separately)

The [DM-NVX-385](#) is a compact DM NVX® AV-over-IP encoder/decoder designed to function as either a transmitter or receiver. Capable of handling a network AV installation of any size, the DM-NVX-385 includes features such as secure web-based control and management, a scaling HDMI output, video wall processing, an analog audio input or output<sup>5</sup>, native AES67 transmit and receive capability, surround sound audio with downmixing, support for copper and fiber-optic Ethernet connectivity, and USB 2.0 and KVM integration.<sup>2, 3</sup>

### HDMI® and USB-C® 4x1 Input Auto-Switching

The DM-NVX-385 includes two HDMI inputs and two USB-C inputs that comprise a 4x1 input switcher. Switching between the four inputs can be performed automatically using auto-switching mode, programmatically via a control system, or through the web interface. When mounted behind a conference room display device, the HDMI input provides a convenient way to connect a Crestron [AirMedia®](#) presentation gateway, video-conferencing codec, or small form factor computer. The USB-C inputs allow for a DisplayPort™ Alt Mode video connection to laptops that do not feature an HDMI connection. The USB-C connectors also pass USB 2.0 data back and forth from the host PC and other DM NVX or DM NUX endpoints.

### Real-Time 4K60 Video Distribution

DM NVX technology ensures real-time, full-motion 4K60 and 5K video performance for the presentation of multimedia, videoconferencing, and live camera images. Interactive functions such as gameplay and using a mouse are fluid and natural. Line-synchronized outputs ensure synchronization of content across multiple displays for applications such as digital signage and video walls. Variable Multicast TTL (Time To Live) enables traversing multiple network routers.

### Support for 5K Resolutions

The DM-NVX-385 includes support for 5K Ultra-Wide 5120 × 2160 and 5K Super-Wide 5120 × 1440 video resolutions, expanding the DM NVX product family's compatibility with the latest generation of computers, monitors, and displays.

### Pixel Perfect Processing Technology

A DM NVX system incorporates Pixel Perfect Processing technology, which provides flawless video transport in all applications. Depending on the operating mode, the DM-NVX-385 can encode or decode a video signal to achieve imperceptible end-to-end latency of less than one frame. The image quality of the source is maintained across a 1-Gigabit network at resolutions up to 5K Ultra-Wide 4:4:4.

### Enterprise-Grade Security

Using advanced security features and protocols such as 802.1X authentication, Active Directory® credential management, AES-128 content encryption, PKI authentication, TLS, SSH, and HTTPS, a DM NVX system

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

delivers a true enterprise-grade network AV solution engineered to fulfill demanding IT policies.

### Encoder and Decoder Functionality

The DM-NVX-385 is configurable to operate as either a network AV encoder or decoder. As an encoder, the connected media source can be transmitted over the network to one or many decoders. As a decoder, the device feeds the received signal to a connected display device, and can quickly switch between multiple encoder feeds. The operating mode can be reconfigured dynamically in less than 1 minute via a control system or web browser or can be changed by using the **SETUP** button

### HDMI Output with 5K Scaler

Whether configured as an encoder or decoder, the built-in scaler ensures an optimal image, scaling the encoded source resolution up or down to match the native resolution of the display device.<sup>4</sup>

### Video Wall Processing

A video wall composed of up to 64 individual displays can be configured using multiple DM NVX endpoints. Each endpoint provides fully adjustable zoom capability and bezel compensation to accommodate a range of video wall configurations and display types. One DM NVX endpoint is required per display, supporting configurations of up to eight wide by eight high.

### 7.1 Surround Sound Audio with Downmixing

DM NVX technology supports the lossless transport of 7.1 surround sound audio signals, including Dolby® TrueHD, Dolby Atmos®, DTS HD®, DTS:X®, and uncompressed linear PCM. The DM-NVX-385 can decode the incoming multichannel surround sound signal from the network or an HDMI input and then downmix that signal to stereo. The stereo downmix signal is automatically routed to the analog output<sup>5</sup>, while the HDMI output can be configured to output either stereo or multichannel signals. As an encoder, the DM-NVX-385 distributes both stereo and multichannel signals simultaneously over the network, allowing either signal to be selected at any decoder on the network.

### Audio Embedding and De-embedding

AES67 support via native integration of Crestron DM NAX® Audio-over-IP technology allows the selected audio source to be transmitted as a 2-channel AES67 source. Another AES67 2-channel audio stream can be received from a Crestron DM NAX device or other AES67 capable device simultaneously and combined with the video signal.

In DM NVX encoder mode, the received AES67 audio stream can be output via the local HDMI output, primary AV stream, secondary audio stream, and analog audio output. In DM NVX decoder mode, the AES67 received audio stream can be

combined with the video and then output via the HDMI output and analog audio output.

An unbalanced stereo analog audio port is also included, which can be configured as either an input or output.<sup>5</sup>

### Copper or Fiber Ethernet Connectivity

The DM-NVX-385 includes two RJ-45 1000BASE-T ports (Ethernet ports 1 and 2) and one SFP port (Ethernet port 3). Any Ethernet port can be used to transport video over a Gigabit Ethernet network. The ports can also be used to daisy-chain multiple endpoints feeding a single-source video wall or individual displays that show the same video image.<sup>2</sup>

A DM NVX system can be deployed on an existing corporate or campus network or on a dedicated network. For information about network requirements and guidelines, refer to the [DM NVX AV-over-IP System Design Guide](#).

### USB 2.0 and KVM Integration

DM NVX technology supports the extension of USB signals, which can be switched and routed alongside the AV signal or separately via a control system. USB 2.0 ports are provided on the DM-NVX-385, allowing a USB mouse, keyboard, or other peripheral device to be connected to a remote endpoint and routed to a computer or other host at the local endpoint.<sup>8</sup>

USB 2.0 Layer 3 data transport supports USB signal extension in DM NVX point-to-point applications across VLANs.

### Streamlined Management Using DM NVX Director® Virtual Switching Appliances

Use of a DM NVX Director® virtual switching appliance ([DM-NVX-DIR-80](#), [DM-NVX-DIR-160](#), or [DM-NVX-DIR-ENT](#)) streamlines the configuration and control process. A DM NVX Director appliance provides a central point of management and enables the creation of multiple virtual matrix switchers through one easy-to-use web-based portal.

### Crestron XiO Cloud® Service Support

The DM-NVX-385 is compatible with the Crestron XiO Cloud® service for remote provisioning, monitoring, and managing. This service enables installers and IT managers to deploy and manage thousands of devices simultaneously. Refer to [crestron.com/xiocloud](http://crestron.com/xiocloud) for more information.

### Low-Profile Installation

The DM-NVX-385 mounts conveniently to a flat surface or rack rail, and fits easily behind a flat panel display, above a ceiling-mounted projector, beneath a tabletop, or inside a lectern, AV cart, or equipment cabinet. Power is provided using POE++ or the optional Crestron [PW-2420RU](#) power pack (sold separately).<sup>7</sup>

Refer to the [DM NVX feature page](#) for additional design tools and reference documents.

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

### Specifications

#### Encoding/Decoding

**Video Codec** **Encoder:** Pixel Perfect Processing (default) or DM-NVX-D10/D20/D200<sup>10</sup>, H.264 AV-over-IP streaming;

**Decoder:** Pixel Perfect Processing or DM-NVX-D10/D20<sup>10</sup>

**Video Resolutions** Up to 5120x2160 @30 Hz (5K Ultra-Wide) or 5120x1440 @60 Hz (5K Super-Wide); Up to 4:4:4 color sampling; HDR10, HDR10+, Dolby Vision, and Deep Color support

**Audio Formats** Primary multichannel (up to 8-channel LPCM or encoded HBR 7.1 surround sound), secondary 2-channel LPCM

**Bit Rates** 200 to 950 Mbps<sup>9</sup>

**Streaming Protocols** RTP, SDP

**Container** MPEG-2 transport stream (.ts)

**Session Initiation** Multicast via secure RTSP

**Copy Protection** HDCP 2.3, AES-128, PKI

**Copy Protection**

HDCP 2.3

**Maximum Resolutions**

Common resolutions are shown in the following table. Custom resolutions are supported at pixel clock rates up to 600 MHz.

#### Video

**Input Signal Types** HDMI with HDR10, HDR10+, Dolby Vision, Deep Color, and 5K support<sup>1,11</sup> (Dual-Mode DisplayPort™ interface and DVI compatible<sup>12</sup>)

DisplayPort over USB-C (DisplayPort Alt Mode)<sup>13</sup> with HDR10, HDR10+, and 5K support

**Output Signal Types** HDMI with HDR10, HDR10+, Dolby Vision, Deep Color, and 5K support<sup>1</sup> (DVI compatible<sup>12</sup>)

**Switcher** 4x1 in encoder mode (Two HDMI, Two USB-C), manual or auto-switching, breakaway audio,<sup>6</sup> Crestron QuickSwitch HD™ technology

5x1 in decoder mode (HDMI, Stream), manual or auto-switching, breakaway audio,<sup>6</sup> Crestron QuickSwitch HD™ technology

**Scaler (Decoder Mode Only)** 5K video scaler with motion-adaptive deinterlacing, intelligent frame rate conversion, Deep Color support, HDR10, HDR10+, and Dolby Vision support, widescreen format selection (zoom, stretch, maintain aspect ratio, or 1:1), video wall processing up to 8 wide x 8 high, static or dynamic text overlay

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

Scan Type	Resolution	Frame Rate	Color Sampling	Color Depth
Progressive	5120x2160 5K Ultra-Wide	30 Hz	4:4:4	8 bit
	5120x2160 5K Ultra-Wide*	60 Hz	4:2:0	8 bit
	5120x1440 5K Super-Wide	60 Hz	4:4:4	8 bit
	4096x2160 DCI 4K and 3840x2160 4K UHD	30 Hz	4:4:4	12 bit
		60 Hz	4:2:0	12 bit
		60 Hz	4:2:2	12 bit
		60 Hz	4:4:4	8 bit
	2560x1600 WQXGA Reduced Blanking	60 Hz	4:4:4	8 bit
	2560x1440 WQHD Reduced Blanking	60 Hz	4:4:4	8 bit
		120 Hz	4:4:4	8 bit
	2560x1080 UWFHD	60 Hz	4:4:4	8 bit
	2048x1152 QWXGA	60 Hz	4:4:4	12 bit
	2048x1080 DCI 2K	60 Hz	4:4:4	12 bit
	1600x1200 UXGA	60 Hz	4:4:4	12 bit
1920x1200 WUXGA	60 Hz	4:4:4	12 bit	
1920x1080 FHD 1080p	60 Hz	4:4:4	12 bit	
	120 Hz	4:4:4	8 bit	
	240 Hz	4:4:4	8 bit	
Interlaced (Input Only)	1920x1080 HD 1080i	30 Hz	4:4:4	12 bit

\*5K Ultra-Wide @60Hz 4:2:0 is supported as an unscaled pass-through resolution only.

### Audio

**Input Signal Types** HDMI (Dual-Mode DisplayPort interface compatible<sup>12</sup>), DisplayPort over USB-C (DisplayPort Alt Mode),<sup>13</sup> eARC (via **HDMI OUT**), AES67 (2-channel), BTS (multichannel network stream), analog stereo<sup>5</sup>

**Output Signal Types** HDMI (multichannel pass-through), eARC (via **HDMI IN 2**), AES67 (2-channel), BTS (multichannel network stream), analog stereo (2-channel)

**Digital Formats** Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos, DTS®, DTS ES, DTS 96/24, DTS HD High Res, DTS HD Master Audio, DTS:X, LPCM up to 8 channels

**Analog Formats** Stereo 2-channel

**Analog-to-Digital Conversion** 24-bit, 48 kHz

**Digital-to-Analog Conversion** 24-bit, 48 kHz

**AES67 or DM NAX Audio-over-IP** 24-bit, 48 kHz

**Analog Performance** Frequency Response: 20 Hz to 20 kHz ±0.5 dB;  
S/N Ratio: >95 dB 20 Hz to 20 kHz A-weighted;  
THD+N: <0.005% @ 1 kHz;  
Stereo Separation: >90 dB

**Analog Output Volume Adjustment** -80 to +20 dB

### Communications

**Ethernet** Auto-switching, auto-negotiating, autodiscovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), IEEE 802.1X, IPv4, IPv6, Active Directory authentication, variable Multicast TTL, HTTPS web browser setup and control, Crestron 3-Series or later control system integration

**USB** USB 2.0 host or device signal extension and routing, Layer 2 or Layer 3

**HDMI** HDCP 2.3, EDID, CEC, ARC, eARC

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

<b>USB-C (DisplayPort Alt Mode)<sup>13</sup></b>	HDCP 2.3, EDID, CEC, USB 2.0
<b>DM NVX (via Ethernet)</b>	HDCP 2.3, AES-128 AV content encryption with PKI authentication, RTP, secure RTSP, SDP, ONVIF, IGMPv2, IGMPv3, SMPTE 2022, FEC (Forward Error Correction)

### Connectors

<b>USB2 TO DEVICE</b>	(1) USB Type-A connector, female; USB 2.0 device port; USB signal extender port for connection to a mouse, keyboard, or other USB 2.0 device; <sup>8</sup> Available Power: 500mA at 5 VDC <sup>14</sup>
<b>HID TO DEVICE</b>	(1) USB Type-A connector, female; USB 2.0 device port; USB signal extender port for connection to a USB HID compliant mouse, keyboard, or other USB HID compliant device; Available Power: 500mA at 5VDC <sup>14</sup>
<b>Ethernet 1 (LAN PoE++)</b>	(1) 8-pin 8P8C connector, female; 100BASE-TX/1000BASE-T Ethernet port; <sup>2</sup> PoE++ PD (powered device) port, IEEE 802.3bt Type 3 Class 6 (60 W) compliant <sup>7, 15</sup>
<b>Ethernet 2 (LAN)</b>	(1) 8-pin 8P8C connector, female; 100BASE-TX/1000BASE-T Ethernet port <sup>2</sup>
<b>Ethernet 3 (1G SFP)</b>	(1) SFP port; Accepts one Crestron SFP-1G Series transceiver module <sup>3</sup>
<b>HDMI OUT (eARC)</b>	(1) HDMI Type A connector, female; HDMI digital video/audio output <sup>1</sup> (DVI compatible); eARC audio return support
<b>HDMI IN 1</b>	(1) HDMI Type A connector, female; HDMI digital video/audio input; <sup>1</sup> (DVI and Dual-Mode DisplayPort interface compatible <sup>12</sup> )
<b>HDMI IN 2 (eARC)</b>	(1) HDMI Type A connector, female; HDMI digital video/audio input; <sup>1</sup> (DVI and Dual-Mode DisplayPort interface compatible <sup>12</sup> ); eARC audio output support
<b>TO HOST DP-S USB2 (IN 3-4)</b>	(2) USB Type-C® connectors, female; USB 2.0 host ports; USB signal extender ports for connection to a computer or other USB 2.0 host; DisplayPort single stream video inputs <sup>13</sup>

<b>AUDIO I/O</b>	(1) 3-pin 3.5 mm detachable terminal block; Unbalanced stereo line-level audio input or output; <sup>5</sup> Input Impedance: 24 kΩ; Maximum Input Level: 2Vrms; Output Impedance: 100 Ω; Maximum Output Level: 2Vrms
<b>IR 1-2</b>	(1) 4-pin 3.5 mm detachable terminal block; Comprises (2) IR/Serial ports; IR output up to 1.1 MHz; 1-way serial TTL (0-5 V) up to 19200 baud; <a href="#">IRP2</a> emitter sold separately
<b>COM</b>	(1) 5-pin 3.5 mm detachable terminal block; Bidirectional RS-232 port; Up to 115.2k baud, hardware and software handshaking support
<b>24VDC 1.5A</b>	(1) 2.1 x 5.5 mm DC power connector; 24VDC power input; <a href="#">PW-2420RU</a> power pack (sold separately)
<b>G</b>	(1) 6-32 screw; Chassis ground lug

### Controls and Indicators

<b>PWR</b>	(1) Bicolor green/amber LED, indicates operating power is being supplied; Amber indicates device is booting; Green indicates device is operational
<b>SETUP</b>	(1) Red LED and (1) push-button for onscreen IP address display and changing operating modes (TX or RX)
<b>RESET</b>	(1) Recessed push-button for hardware reset
<b>OL</b>	(1) Green LED, indicates an online connection to a control system via Ethernet
<b>TX</b>	(1) Green LED, indicates unit is in encoder (transmitter) mode
<b>RX</b>	(1) Green LED, indicates unit is in decoder (receiver) mode
<b>Ethernet 1-3</b>	(2) LEDs per port; Green indicates Ethernet link status; Amber indicates Ethernet activity
<b>HDMI OUT</b>	(1) Green LED, indicates video signal transmission at the HDMI output
<b>HDMI IN 1-2</b>	(2) Green LEDs, indicates sync detection at the HDMI inputs

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

### Power

**PoE++** IEEE 802.3bt Type 3 Class 6 (60 W) compliant;  
Compatible with PoE++ compliant Ethernet switch or third-party IEEE 802.3bt compliant PSE<sup>15</sup>

**Power Pack (Optional)** Input: 1.5 A maximum @ 100-240 VAC, 50/60 Hz;  
Output: 2.5 A @ 24 VDC;  
Model: [PW-2420RU](#) (sold separately)

### Environmental

**Temperature** 32° to 104°F (0° to 40°C)  
**Humidity** 10% to 90% RH (noncondensing)  
**Heat Dissipation** 85 BTU/hr  
**Acoustic Noise** 33 dBA typical

### Construction

**Chassis** Metal, black finish, integral mounting flanges, fan cooled;  
Vented top, front, rear, and sides  
**Mounting** Freestanding, surface mount, or attachment to a single rack rail

### Dimensions

**Height** 8.21 in. (209 mm)  
**Width** 8.21 in. (209 mm)  
**Depth** 1.22 in. (31 mm)

### Weight

2.81 lb (1.27 kg)

### Compliance

**Regulatory Model: M202234002**

FCC Part 15 Class B, IC Class B, CE, Intertek® Listed for US and Canada

### Model

**DM-NVX-385**

DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

### Available Accessories

For a list of available accessories, visit the [DM-NVX-385](#) product page.

### Management Tools

**DM-NVX-DIR-80**

DM NVX® Director® Virtual Switching Appliance for 80 Endpoints

**DM-NVX-DIR-160**

DM NVX® Director® Virtual Switching Appliance for 160 Endpoints

**DM-NVX-DIR-ENT**

DM NVX® Director® Virtual Switching Appliance for 1000 Endpoints

#### Notes:

- 5K performance and HDR support require the use of HDMI cables and couplers with a minimum TMDS bandwidth of 18 Gbps. If 4K60 4:2:0 or 4K30 4:4:4 performance is acceptable, cables and couplers with a minimum bandwidth of 10.2 Gbps may be used. Bandwidth loss is cumulative; therefore, performance may be reduced when inserting multiple cables and couplers inline.
- The minimum cable required for DM NVX over 1000BASE-T Ethernet (copper) is unshielded CAT5e. All Ethernet ports on the DM-NVX-385 are for connection to an Ethernet network or device. The Ethernet ports cannot be connected to the DM® ports of other Crestron DigitalMedia™ devices.
- Use of the SFP port requires the purchase of a Crestron SFP-1G Series transceiver module (sold separately). All Ethernet ports on the DM-NVX-385 are for connection to an Ethernet network or device. The Ethernet ports cannot be connected to the DM® ports of other Crestron DigitalMedia™ devices.
- When the DM-NVX-385 is in encoder mode, the HDMI output resolution is matched to the resolution of the encoded source.
- The analog audio port can function as either an input or output, but not both.
- Combining audio from one encoder with video from another encoder is possible using the secondary 2-channel audio stream only. Multichannel audio from one encoder cannot be combined with video from another encoder.
- Refer to the "Power" section for powering options.
- The DM-NVX-385 can accept a USB device or a USB host device connection, not both simultaneously. Crestron DM NVX products are engineered to deliver maximum compatibility with the widest possible range of USB products. Crestron does not guarantee that all USB products are compatible with DM NVX products. Consult the [DM NVX AV-over-IP System Design Guide](#) for USB bandwidth considerations.
- The minimum bit rate for 4K60 video is 350 Mbps. A bit rate below 350 Mbps may display a black screen.

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

10. In encoder mode, the stream type of the DM-NVX-385 must be set by using the web interface or a control system. The default setting is Pixel Perfect Processing for interoperability with DM NVX 4K60 4:4:4 decoders. For interoperability with a DM-NVX-D10, DM-NVX-D20, or DM-NVX-D200 decoder, the stream type of the DM-NVX-385 encoder must be set to DM-NVX-D10/D20 Series. In addition, the resolution of the encoder must be set so that it does not exceed the maximum resolution of the DM-NVX-D10, DM-NVX-D20, or DM-NVX-D200 decoder.

In decoder mode, the proper stream type of the DM-NVX-385 is automatically used. For interoperability with DM NVX 4K60 4:4:4 encoders, Pixel Perfect Processing is automatically used as the stream type of the DM-NVX-385 decoder. For interoperability with DM-NVX-E10/E20 Series encoders, DM-NVX-D10/D20 Series is automatically used as the stream type of the DM-NVX-385 decoder.

11. 3D formats are not supported.
12. HDMI connections require an appropriate adapter or interface cable to accommodate a DVI or Dual-Mode DisplayPort signal. [CBL-HD-DVI](#) interface cables are available separately.
13. USB-C connections require USB-C cables that support DisplayPort Alt Mode video in order to pass video signal. Not all USB-C cables can support DisplayPort Alt Mode video.
14. When PoE++ is used to power the DM-NVX-385, a maximum of 500mA is available to power both the USB TO DEVICE and USB HID ports. To prevent possible instability issues, it is recommended that a [PW-2420RU](#) power pack (sold separately) be used.
15. In order for Ethernet port 1 to receive PoE++, the port requires connection to a PoE++ compliant Ethernet switch or other equipment that has a PoE++ PSE port. Cabling that connects to a PoE++ PSE port is designed for intrabuilding use only.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or contact us for additional information by visiting [www.crestron.com/contact/our-locations](http://www.crestron.com/contact/our-locations) for your local contact.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

The product warranty can be found at [www.crestron.com/warranty](http://www.crestron.com/warranty).

The specific patents that cover Crestron products are listed online at [www.crestron.com/legal/patents](http://www.crestron.com/legal/patents).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, 3-Series, .AV Framework, AirMedia, Crestron Home, DigitalMedia, DM, DM NAX, DM NVX, DM NVX Director, QuickSwitch HD, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby, Dolby Atmos, Dolby Digital, and Dolby Vision are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS HD, and DTS:X are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Intertek is either a trademark or registered trademark of Intertek Group in the United States and/or other countries. Active Directory is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. USB-C and USB Type-C are either trademarks or registered trademarks of USB Implementers Forum, Inc. in the United States and/or other countries. DisplayPort is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

### HDMI

Specifications are subject to change without notice.

©2026 Crestron Electronics, Inc.

Rev 05/07/26

# DM-NVX-385

## DM NVX® 5K 4x1 AV-over-IP Switcher with HDMI® and USB-C® Connectivity and Downmixing

