

USB-EXT-2-LOCAL/USB-EXT-2-REMOTE

USB over Category Cable Extenders



- Provide reliable, high-speed USB signal extension for most USB 1.1 or 2.0 devices¹
- Compatible with Crestron® USB over Category Cable Extender Wall Plates ([USB-EXT-2-LOCAL-1G](#) and [USB-EXT-2-REMOTE-1G](#))
- Extend USB signals up to 330 ft (100 m) over CAT5e (or better) twisted-pair cable²
- 100-240 VAC power supply (included with the Remote extender)
- Enable transparent point-to-point USB extension without any configuration or programming
- Plug-and-play compatible with most types of USB 1.1 and 2.0 devices and hosts¹
- No drivers required with Windows®, macOS®, or Linux® operating systems¹
- Transport USB over CAT5e at speeds up to 480 Mbps
- Mass Storage Acceleration maximizes USB 2.0 bulk transfer speeds
- Expandable using up to 4 USB hubs (not included)
- USB-EXT-2-REMOTE provides 2 USB Type A ports

The Crestron® USB over Category Cable Extenders ([USB-EXT-2-LOCAL](#) and [USB-EXT-2-REMOTE](#)) deliver reliable, high-speed USB signal extension for USB 1.1 and 2.0 devices in a conference room, classroom, auditorium, command center, medical facility, public space, or residence. Without requiring any special configuration or drivers, the USB extenders enable wire runs up to 330 ft (100 m) over a single CAT5e (or better) shielded twisted-pair (TP) cable. The USB extenders support most USB device types and are plug-and-play compatible with computers running Windows®, macOS®, and Linux® operating systems.

Two types of USB extenders are available:

- USB-EXT-2-REMOTE - Provides connectivity for up to two USB devices (keyboards, whiteboards, mobile devices, etc.) at one location
- USB-EXT-2-LOCAL - Provides connectivity for a single USB host (computer, media server, codec, etc.)

Linking the two extenders requires one run of CAT5e shielded twisted-pair cable.² Both extenders are powered by a single 100-240 VAC power supply, which can be connected at either end to an AC power receptacle.³ The USB-EXT-2-LOCAL and USB-EXT-2-REMOTE are compatible with the USB over Category Cable Extender Wall Plates ([USB-EXT-2-LOCAL-1G](#) and [USB-EXT-2-REMOTE-1G](#)) via the LINK connection.

NOTES:

- USB-EXT-2-LOCAL-1G and USB-EXT-2-REMOTE-1G power sources cannot power USB-EXT-2-LOCAL and USB-EXT-2-REMOTE.
- The USB-EXT-2-LOCAL and USB-EXT-2-REMOTE are simple point-to-point USB signal extenders. They do not switch or route USB signals, and do not connect to a network. For KVM and other applications routing USB signals over an Ethernet network, please refer to the USB over Category Cable Extenders ([USB-NX2-LOCAL-1G](#) and [USB-NX2-REMOTE-1G](#)) or the USB over Ethernet Extenders with Routing ([USB-EXT-DM-LOCAL](#) and [USB-EXT-DM-REMOTE](#)).²

USB-EXT-2-LOCAL/USB-EXT-2-REMOTE

USB over Category Cable Extenders

Specifications

Communications

Link	USB extension up to 330 ft (100 m) over solid-core CAT5e (or better) unshielded twisted pair (UTP) cable ²
USB Device Support	USB 1.0/1.1 and 2.0 compatible including mass storage and isochronous devices ¹
USB Hub Support	Any signal chain may include up to 4 USB hubs plus one USB-EXT-2-LOCAL and one USB-EXT-2-REMOTE ¹
Maximum USB Devices	30 USB devices, or 4 USB hubs with 26 USB devices
Host Computer OS Support	Windows®, macOS®, and Linux® operating systems
USB Throughput	USB 2.0 up to 480 Mbps, USB 1.1 up to 12 Mbps

Connectors – Local extender

24V 1A	(1) 2.1 x 5.5 mm DC power connector; 24 VDC power input; PW-2412WU (power supply included with the Remote extender) ³
Config	For factory use only
Link	(1) 8-pin RJ-45 connector, female; Connects directly to a Remote extender ²
USB	(1) USB Type B connector, female (USB B to A cable included) USB 2.0 device port for connection to the USB host computer, media server, game console, annotator, codec, etc. ; Provides power from the source

Connectors – Remote extender

24V 1A	(1) 2.1 x 5.5 mm DC power connector; 24 VDC power input PW-2412WU (power supply included) ³
Config	For factory use only
Link	(1) 8-pin RJ-45 connector, female; Connects to Link port on the Local extender ²
USB	(2) USB Type A connectors, female; USB 2.0 host ports for connection of USB devices such as mice, keyboards, and other USB devices ¹ Available USB Power: 1A maximum per port, 1.5A maximum total

Indicators – Local extender

Activity	(1) Amber LED, indicates data activity the Link
Host	(1) Green LED, indicates a valid connection to the USB host
Link	(1) Green LED, indicates a valid Link connection to the Remote extender
Power	(1) Blue LED, indicates operating power is supplied via the

Indicators – Remote extender

Activity	(1) Amber LED, indicates data activity the Link
Host	(1) Green LED, indicates a valid connection to the USB host
Link	(1) Green LED, indicates a valid Link connection to the Remote extender
Power	(1) Blue LED, indicates operating power is supplied via the

Power

Available USB Power	Supplies 1A maximum per each of two USB Type A ports, 1.5A maximum total
USB-EXT-2-LOCAL	USB bus power; (power supply included with Remote extender) ³
USB-EXT-2-REMOTE	Input: 100-240VAC, 50/60 Hz; Output: 0.75A @ 24VDC ³

Environmental

Temperature	32° to 122°F (0° to 50°C)
Humidity	20% to 80% RH (non-condensing)

Construction

Housing	Metal, black finish, adhesive rubber feet
Mounting	Includes four slots for wire ties or other third-party mounting hardware

Dimensions

Height	1.03 in. (26 mm) without feet
Width	2.96 in. (75 mm)
Depth	3.43 in. (87 mm)

Compliance

CE, IC, FCC Part 15 Class B digital device

USB-EXT-2-LOCAL/USB-EXT-2-REMOTE

USB over Category Cable Extenders

Models

USB-EXT-2-LOCAL

USB over Category Cable Extender, Local

USB-EXT-2-REMOTE

USB over Category Cable Extender, Remote

USB-EXT-2 KIT

USB over Category Cable Extender, Local and Remote

Notes:

1. The USB extender is engineered to deliver maximum compatibility with the widest possible range of devices. Crestron does not guarantee that all USB devices or hosts are compatible with the USB extender. Certain USB devices may require additional driver installation if not directly supported by the computer's operating system.
2. For a direct link connection (not on a network) between the Local and Remote extenders, as a minimum, use high quality, solid core CAT5e (or better) unshielded twisted pair (UTP) cable. If connecting either extender through a wall jack, a stranded patch cord may be used. The maximum aggregate cable length is 330 ft (100 m) between units. The minimum cable length is 6 ft (1.8 m). Do not connect the Link ports to an Ethernet LAN or any other network or device, including the USB-EXT-DM-REMOTE, USB-EXT-DM-LOCAL, DM-NUX-R2-1G, DM-NUX-L2-1G.
3. Use the power supply included with the Remote extender on the Remote extender. The power supply may be used on the Local extender only when the Link port on the Local extender is connected to the Link port on the Remote extender. If the power supply is connected to the Local extender and the Link port is connected to a network device (not recommended), the network device may become overloaded and damaged.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.

©2025 Crestron Electronics, Inc.
Rev 08/21/25

USB-EXT-2-LOCAL/USB-EXT-2-REMOTE

USB over Category Cable Extenders

