# Wall Mount IR Gateway

The C2N-IRGW-1G IR Gateway is a 1-way infrared receiver for Crestron IR wireless handheld remotes and touchpanels. It is also compatible with third-party IR remotes utilizing the RC5 command set.

The C2N-IRGW-1G is designed to fit in a 1-gang electrical box using a decorator style faceplate (not included). Its entire visible face consists of a smoked plastic lens providing a neutral appearance suitable for use with any color scheme. The C2N-IRGW-1G is a Cresnet device compatible with any 2-Series control system.

### **SPECIFICATIONS**

### **IR Wireless**

IR Frequency: 36 to 38 kHz IR Formats: Crestron format, RC5

Range: Up to 50 ft line of sight (typical), dependent upon angle, obstructions, IR interference, and IR remote signal

strength

### Connectors

NET: 4-pin 3.5mm detachable terminal block;

### **LED Indicators**

(1 red) Indicates IR signal reception, Cresnet network communication, and setup/update functions

### Controls

(1) Recessed miniature pushbutton for setup

### Power Requirements

Cresnet Power Usage: 1 Watt (0.042 Amps @ 24 Volts DC)

## **Environmental**

Temperature: 41° to 104°F (5° to 40°C)

Humidity: 10% to 90% RH (non-condensing)



### **Enclosure**

Injection-molded plastic with smoked plastic face, 1-gang mountable in an electrical box using decorator style faceplate (not included)

### Dimensions (Without Faceplate)

Height: 4.13 in (10.48 cm) Width: 1.75 in (4.45 cm) Depth: 1.37 in (3.45 cm)

### Weight

2.4 oz (68.0 g)

### **ACCESSORIES**

CRESNET-HP-NP-TL-SP1000:

CRESNET-NP-BK-B500:

CRESNET-P-BK-SP500:

CRESNET-NP-TL-SP1000:

CRESNET-P-TL-SP1000:

FP-G1-A-S:


FP-G1-B-S:




Wall Mount IR Gateway FP-G1-W-S:




# Wall Mount IR Gateway





# 3.38 in (8.33 cm) 3.81 in (9.68 cm)



# Wall Mount IR Gateway

