

CLCI-1SW2EX-W

In-Ceiling Switch, 2 Channels, infiNET EX® Wireless, 230VAC

The CLCI-1SW2EX-W is a two-channel switch capable of controlling two independent, 230VAC lighting loads. Its ultra-slim design allows it to be installed in the ceiling, either next to or near the fixture. The CLCI-1SW2EX-W communicates with the Crestron control system using infiNET EX® wireless technology, making it perfect for both new and retrofit applications.

The CLCI-1SW2EX-W installs inline without requiring special wiring and can be controlled via a standard light switch.

Two-Channel Switching

The CLCI-1SW2EX-W switches incandescent, tungsten-halogen, magnetic low-voltage, electronic low-voltage, fluorescent ballast, neon/cold cathode, and motor loads for each of the two independent channels. Two sets of screw terminals (internally wired in parallel) enable easy wiring to each load of up to 500 VA.

Easy Loop-Thru Wiring

The CLCI-1SW2EX-W is powered using a set of high-voltage screw terminals and has a second set of terminals that are wired in parallel to easily daisy-chain additional CLCI-series devices. This provides a fast, clean installation when deploying multiple CLCI- devices and eliminates the need for additional wire connectors or extra gang boxes. In some retrofit applications, this lets you create more zones from what was originally wired.

Out-of-the-Box Control via Standard Switch

The CLCI-1SW2EX-W provides built-in support for applications that require basic load control using a cost effective maintained or momentary switch to control the load. Use a maintained or momentary switch to perform basic on and off control.

Complete Crestron Control



A Crestron control system connection allows the CLCI-1SW2EX-W to be controlled from any keypad, touch panel, remote, or mobile device. Tie in occupancy sensors and photocells together with Crestron Fusion® software for a complete solution to effectively manage energy.

Simple Setup

Setup is simple, especially when using a connected maintained or momentary switch. A specific series of button presses initiates the wireless device acquire mode, so there's no need to climb a ladder to join the device to the infiNET EX network.

infiNET EX® Wireless Communications

infiNET EX wireless technology provides two way RF communications throughout a residential or commercial structure without the need for physical control wiring. Each infiNET EX device acts as an expander by sending command signals to other infiNET EX devices in range (approximately 150 ft (46 m) indoors) to ensure reliability and stability.

The device communicates with a control system via a **Crestron**

Wireless Gateway (sold separately). Up to 100 infiNET EX

CLCI-1SW2EX-W

In-Ceiling Switch, 2 Channels, infiNET EX® Wireless, 230VAC

devices may coexist on a wireless network.

Note: Any infiNET EX device that provides expander functionality will effectively extend the range of the wireless network beyond the initial range of the gateway. Battery-powered infiNET EX devices do not provide expander functionality. A dedicated infiNET EX Wireless Expander is also available (**CLW-EXPEX**, sold separately).

SPECIFICATIONS

Power Requirements

Line Power

:
220 to 240VAC, 50/60Hz

Load Ratings

Control Channels

:
2

Maximum Load per Channel

:
2AX (2A fluorescent)

Load Types

:
Incandescent, tungsten-halogen, magnetic low-voltage, electronic low-voltage, fluorescent ballast, neon/cold cathode, motor

Wireless

RF Transceiver

Internal wiring in parallel

N

:
(2) Captive screw terminals for connecting to neutral AC;

Internal wiring in parallel

G

:
(2) Captive screw terminals for connecting to earth ground;
Internal wiring in parallel

R

:
(1) Captive screw terminal for connecting to remote switch;
Remote switch wires to L and R; consult manual for more information

N1

:
(1) Captive screw terminal for load connections, channel 1;
Neutral to load

SL1

:
(1) Captive screw terminal, channel 1;
Switched line power to load

N2

CLCI-1SW2EX-W

In-Ceiling Switch, 2 Channels, infiNET EX® Wireless, 230VAC

Plastic surface-mount housing, suitable for installation in a nonplenum ceiling space

Dimensions

Height

:

41 mm (1.61 in.)

Width

:

178 mm (7 in.)

Depth

:

55 mm (2.13 in.)

Weight

199 g (7 oz)

Compliance

Regulatory Model: CLCI-1SW2EX

CE, RCM;

In the CSEA region, available in Macau & Hong Kong only.

To search for product certificates, refer to

support.crestron.com/app/certificates.

Notes:

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or

Crestron Electronics, Inc. 15 Volvo Drive | Rockleigh, NJ 07647

Tel: 800.237.2041 / 201.767.3400 | Fax: 201.767.1905



CLCI-1SW2EX-W

In-Ceiling Switch, 2 Channels, infiNET EX® Wireless, 230VAC

In-Ceiling Wireless Lighting Control

