CNXRMIRD

IR Receiver

The CNXRMIRD is an optional infrared (IR) receiver designed for use with a control system or room solution box that includes an IR input port. The CNXRMIRD affords cost-effective control from any Crestron or third-party universal IR remote utilizing the RC5 command set.

SPECIFICATIONS

IR Wireless

IR Frequency: 36 to 38 kHz IR

Format: Crestron format, RC5

Range: Up to 50 ft line of sight (typical), dependent upon angle, obstructions, IR interference, and IR remote signal strength

Connectors

(1) Attached 6 ft (1.83 m) long cable with 3.5 mm mini phone plug (male) for connection to a Crestron IR IN port, extendable up to 500 feet;

Environmental

Temperature: 41° to 104° F (5° to 40° C)

Humidity: 10% to 90% RH (non-condensing)

Enclosure

Black plastic cube

Dimensions

Height: 1.0 in (2.54 cm)

Width: 1.0 in (2.54 cm)

Depth: 1.0 in (2.54 cm)

Weight

2.4 oz (68.0 g)

CNXRMIRD

IR Receiver



Crestron Electronics, Inc. 15 Volvo Drive | Rockleigh, NJ 07647
Tel: 800.237.2041 / 201.767.3400 | Fax: 201.767.1905

CNXRMIRD

IR Receiver





All brand names, product names and trademarks are the property of their respective owners.
©2026 Crestron Electronics, Inc. | 15 Volvo Drive | Rockleigh, NJ 07647