

Zūm™ J-Box Accessory Power Supply

- > Provides a means for adding a Zūm™ Network Bridge or Contract Closure Output to a Zūm lighting system^[1]
- > Zūm Mesh peer-to-peer RF communications^[2]
- > Pair and play wireless integration with Zūm dimmers, switches, occupancy sensors, vacancy sensors, and daylight sensors^[1]
- > 100-277 Volts AC line powered
- > Flying lead wiring connections
- > Knockout mount to a standard 4-inch square junction box
- > UL® 2043 listed for installation in an environmental air handling space
- > Meets UL 916 standard for energy management equipment
- > Meets CEC Title 24 energy efficiency standards^[3]
- > Meets ASHRAE® 90.1 energy efficiency standards^[4]
- > ICC® International Energy Conservation Code® compliant^[5]

The ZUMMESH-JBOX-PSU is an accessory power supply that mounts to a four inch square junction box and provides a host for a Zūm™ Network Bridge (ZUMMESH-NETBRIDGE^[1]) or Zūm Contact Closure Output (ZUMMESH-CCO^[1]). It communicates wirelessly with other Zūm Mesh devices in a Zūm commercial room lighting system to enable centralized monitoring and management using the network bridge, or to enable integration with an HVAC system using the contact closure output.

The ZUMMESH-JBOX-PSU is similar to a ZUMMESH-JBOX load controller, but without any dimming or switch circuitry onboard.

Please refer to the [Zūm Lighting Control System Setup Guide \(Doc # 7957\)](#) for additional information.

SPECIFICATIONS

Wireless Communications

RF Transceiver: Zūm Mesh & Zūm Net 2-way RF, 2.4 GHz ISM Channels 15, 20, 25, or 26 (channel auto-selected), IEEE 802.15.4 compliant

Zūm Mesh Range: 50 ft (15 m) to nearest Zūm Mesh peer-to-peer mesh network device(s), subject to site-specific conditions and individual device capabilities^[2]

Zūm Net Range: 50 ft (15 m) to a Zūm Net wireless gateway or nearest Zūm Net mesh network device(s), requires the Zūm Network Bridge (model ZUMMESH-NETBRIDGE^[1]), range between floors or ceilings is limited to one level, subject to site-specific conditions and individual device capabilities^[2]

Note: A maximum of 32 Zūm Mesh wireless devices is permitted per room. Only one Network Bridge is permitted per room.

Controls & Indicators

SETUP: (1) Pushbutton and (1) red LED, used for room setup and factory reset

TEST: (1) Pushbutton and (1) green LED, used for room setup and factory reset



Zūm J-Box Accessory Power Supply (Right)
Shown with Zūm Network Bridge (Left, sold separately)

Connections

Hot: (1) 14 AWG Class 1 flying lead, black, line power input

Neutral: (1) 14 AWG Class 1 flying lead, white, neutral

Expansion Port: Accessory port for Zūm Network Bridge or Zūm Contact Closure Output (model ZUMMESH-NETBRIDGE or ZUMMESH-CCO^[1])

Power

Line Power: 100-277 Volts AC, 50/60 Hz

Idle Power Consumption: 1 Watt

Environmental

Temperature: 32° to 104° F (0° to 40° C)

Humidity: 10% to 90% RH (non-condensing)

Construction

Housing: Plastic, white, UL 94 5VA flame rated

Mounting: Mounts to the side of a 4-inch square junction box via a 1/2 inch conduit knockout, meets the requirements of UL 2043 for installation in an environmental air-handling (plenum) space

Dimensions

Height: 3.25 in (83 mm)

Width: 4.17 in (106 mm)

Depth: 1.32 in (34 mm)

Note: Projects 3.66 inches (93 mm) from the junction box when installed.

ZUMMESH-JBOX-PSU Züm J-Box Accessory Power Supply

Weight

7 oz (199 g)

Compliance

UL Listed for US & Canada, IC, FCC Part 15 Class A digital device, UL 916, UL 2043, UL 94 5VA, CEC Title 24^[3], ASHRAE 90.1^[4], IECC^[5]

MODELS & ACCESSORIES

Available Models

ZUMMESH-JBOX-PSU: Züm J-Box Accessory Power Supply

Available Accessories

ZUMMESH-NETBRIDGE: Züm Network Bridge

ZUMMESH-CCO: Züm Contact Closure Output

ZUM-FLOOR-HUB: Züm Floor Hub

ZUMNET-GATEWAY: Züm Net Wireless Gateway

Notes:

1. Item(s) sold separately. Refer to each product's spec sheet for more information.
2. "Züm Mesh" refers to the wireless mesh network within each room composed of dimmers, switches, load controllers, keypads, and sensors. "Züm Net" refers to the wireless mesh network that connects one or more rooms with a Züm Floor Hub, and consists of a Züm Net Wireless Gateway and one or more Züm Network Bridges. AC-powered Züm Mesh or Züm Net devices function as routing nodes, which effectively extend the range of a Züm Mesh or Züm Net wireless network. Battery-powered devices only function as leaf nodes and do not extend range. A Züm Mesh network composed predominantly of battery-powered devices may require additional AC-powered devices, such as the ZUMMESH-JBOX-PSU, to serve as supplemental routing nodes to fill any gaps in coverage. Refer to the "Installation and Setup of Crestron RF Products, Best Practices" guide (Doc #6689) for additional guidelines.

3. This product is part of a California Energy Commission Title 24 compliant solution. Refer to <http://www.energy.ca.gov/title24/> to learn more about designing a fully compliant solution. Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>.
4. This product is part of an ASHRAE 90.1 compliant solution. Refer to <https://www.ashrae.org/> to learn more about designing a fully compliant solution. Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>.
5. This product is part of an International Energy Conservation Code compliant solution. Refer to <https://www.iccsafe.org/iecc/> to learn more about designing a fully compliant solution. Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>.

This product may be purchased from an authorized Crestron dealer or distributor. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Additional resources can be accessed via the Crestron Commercial Lighting Consultants Partner Portal at <http://www.crestron.com/about/partner-info/commercial-lighting-consultants>. For assistance with incorporating this product into a design or specification, please contact the Commercial Lighting Consultant Hotline via email at clcdesign@crestron.com or by calling 888-330-1502.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Certain Crestron products contain open source software. For specific information, visit www.crestron.com/opensource.

Crestron, the Crestron logo, and Züm are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. ASHRAE is either a trademark or registered trademark of American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. in the United States and/or other countries. ICC and International Energy Conservation Code are either trademarks or registered trademarks of International Code Council, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of UL LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2017 Crestron Electronics, Inc.

